


TYPICAL INTERSECTION PLAN

NOTES:

- 1.) 1 METRE SEPARATION FROM VERTICAL STRUCTURES TO VENDING BOXES. (IE, LIGHT STANDARD, BENCHES, GARBAGE CANS, PARKING SIGNS, TREES, ETC. THIS INCLUDES MANHOLES, WATER VALVES, DRIVEWAYS, ETC.)
- 2.) VENDING BOX MUST BE WEIGHTED WITH BALLAST TO PREVENT TIPPING.
- 3.) VENDING BOX MUST NOT BE PLACED IN FRONT OF ANY PARKING AREAS.
- 4.) VENDOR BOX ARE SUBJECT TO THE APPROVAL OF WINDSOR TRANSIT, TRANSPORTATION PLANNING, AND THE PLANNING DEPARTMENT.
- 5.) A MINIMUM OF 2.44m (8'-0") CLEARANCE TO MAINTAIN A CLEAR PEDESTRIAN AISLE.

CITY OF WINDSOR	
ENGINEERING DEPARTMENT	
VENDING BOX STANDARD	
DR'N BY: AJC	DATE: JUNE, 2011
REVISION:	CH'KD BY: P. UBENE
CH'KD BY:	PASSED BY:
 CITY ENGINEER	AS-544